




## 2001 OWNER'S MANUAL



Note: Your fork's appearance may vary from the illustrations/photos in this manual.

\* Denotes updated information since the printed version that came with your fork.

**Congratulations!** You have the best in suspension components on your bicycle! This manual contains important information about the safe operation and maintenance of your fork. To insure that your RockShox fork performs properly, we recommend that you have your fork installed by a qualified bicycle mechanic. We also urge you to follow our recommendations to help make your bicycling experience more enjoyable and trouble-free.

## I M P O R T A N T

### Consumer Safety Information

1. Before riding the bicycle, be sure the brakes are properly installed and adjusted. If the brakes do not work properly, the rider could suffer serious and/or fatal injuries.
2. If the fork ever loses oil or if it makes sounds of excessive topping out, stop riding the bicycle immediately and have the fork inspected by a dealer or call RockShox. Continuing to ride with the shock in these conditions could result in loss of control of the bicycle with possible serious and/or fatal injuries.
3. Always use genuine RockShox parts. Use of aftermarket replacement parts voids the warranty and could cause structural failure to the shock. Structural failure could result in loss of control of the bicycle with possible serious and/or fatal injuries.
4. Use extreme caution not to tilt the bicycle to either side when mounting the bicycle to a carrier by the fork drop-outs (front wheel removed). The fork legs may suffer structural damage if the bicycle is tilted while the drop-outs are in the carrier. Make sure the fork is securely fastened down with a quick release. Make sure the rear wheel is fastened down when using ANY bike carrier that secures the fork's drop-outs. Not securing the rear can allow the bike's mass to side-load the drop-outs, causing them to break or crack. If the bicycle tilts or falls out of its carrier, do not ride the bicycle until the fork is properly examined for possible damage. Return the fork to your dealer for inspection or call RockShox if there is any question of possible damage (See the International Distributor List). A fork leg or drop-out failure could result in loss of control of the bicycle with possible serious and/or fatal injuries.
5. Only mount cantilever-type brakes to the existing brake posts. Forks with hangerless style braces are only designed for 'V'- style or hydraulic cantilever brakes. Do not use any cantilever brake other than those intended by the brake manufacturer to work with a hangerless brace. Do not route the front brake cable and/or cable housing through the stem or any other mounts or cable stops. Do not use a front brake cable leverage device mounted to the brace.

**ROCKSHOX FORKS ARE DESIGNED FOR COMPETITIVE OFF-ROAD RIDING AND DO NOT COME WITH THE PROPER REFLECTORS FOR ON-ROAD USE. YOUR DEALER SHOULD INSTALL PROPER REFLECTORS TO MEET THE CONSUMER PRODUCT SAFETY COMMISSION'S (CPSC) REQUIREMENTS FOR BICYCLE STANDARDS IF THE FORK IS GOING TO BE USED ON PUBLIC ROADS AT ANY TIME.**

## I N S T A L L A T I O N

It is extremely important that your RockShox fork is installed correctly by a qualified bicycle mechanic. Improperly installed forks are extremely dangerous and can result in severe and/or fatal injuries.

1. Remove the existing fork from the bicycle and the crown race from the fork. Measure the length of the fork steerer tube against the length of the RockShox steerer tube. The RockShox steerer tube may need cutting to the proper length. Make sure there is sufficient length to clamp the stem (refer to the stem manufacturer's instructions).

### W A R N I N G

DO NOT ADD THREADS TO ROCKSHOX THREADLESS STEERERS. THE STEERER TUBE CROWN ASSEMBLY IS A ONE-TIME PRESS FIT. REPLACEMENT OF THE ASSEMBLY MUST BE DONE TO CHANGE THE LENGTH, DIAMETER OR HEADSET TYPE (THREADED OR THREADLESS).

DO NOT REMOVE OR REPLACE THE STEERER TUBE. THIS COULD RESULT IN THE LOSS OF CONTROL OF THE BICYCLE WITH POSSIBLE SERIOUS AND/OR FATAL INJURIES.

2. Install the headset crown race (26.4mm for 1" steerers, 29.9mm for 1 1/8" steerers) firmly against the top of the fork crown. Install the fork assembly on the bike. Adjust the headset until you feel no play or drag.
3. Install the brakes according to the manufacturer's instructions and adjust brake pads properly. Use the fork only with V-type or hydraulic cantilever brakes mounted to the existing brake posts or disc style brakes mounted through the provided mounting holes. Do not use any cantilever brake other than those intended by the brake manufacturer to work with a hangerless brace.
4. Adjust the front wheel quick release to clear the dropout's counter bore. The quick release nut must be tightened after the wheel is properly seated into the dropout's counter bore. Make sure four or more threads are engaged in the quick release nut when it is closed. Orient the quick release lever in front of and parallel to the lower tube in the locked position.
5. Keep in mind tire clearance as you choose tires. Maximum size is 2.6" wide or 347 mm radius installed. Be sure to check this radius whenever you change tires. To do this, remove the air and compress the fork completely to make sure at least 5mm of clearance exists between the top of the tire and the bottom of the crown. Exceeding maximum tire size will cause the tire to jam against the crown when the fork is fully compressed.

## PERFORMANCE TUNING

RockShox Psylo forks can be tuned for your particular weight, riding style, and terrain.

### Setting Sag

Psylo forks are designed to sag when you are sitting on your bike. Sag is the compression of the fork caused by the rider's weight. Proper sag allows the front wheel to follow the contour of the terrain as you ride. Sag is adjusted by turning the top cap preload adjuster. Turning the adjuster clockwise increases spring preload (i.e. stiffening the spring) decreasing sag. Turning the adjuster counter clockwise decreases spring preload which increases sag.

<u>Fork Travel</u>	<u>Sag</u>
80 mm	13-20 mm
100 mm	18-25 mm
125 mm	20-31 mm

To measure sag, install a zip tie on the upper tube of the fork flush against the XXX seal. Sit on the bike with normal riding apparel. Step off the bike, and measure the distance between the XXX seal and the zip tie. This is your sag. If you're unable to achieve optimum sag by turning the preload adjuster, you may need to change the fork's spring rate.

### Changing the Spring Rate

Spring rate is the amount of force needed to compress a spring one inch. Exchanging your Psylo fork's coil spring for a spring of a higher or lower rate will alter the overall feel of your fork. Higher spring rates make the fork feel more "stiff", while lower spring rates make the fork more "supple". Contact your local RockShox dealer to order replacement springs.

### Vari-Adjust All Travel (Figs. 1-3)

Psylo forks can be adjusted for 80, 100, or 125 mm of travel (or anywhere in between!). To determine the travel on your fork, measure the amount of exposed upper tube (from the bottom of crown to the XXX dust wiper). Compare this measurement to the chart below)

<u>Fork Travel</u>	<u>XXX Seal to Crown</u>
80 mm	100 mm
100 mm	120 mm
125 mm	145mm

#### CHANGING TRAVEL

1. Using a 24mm socket remove the top cap.
2. Remove the coil spring.
3. Insert a long, flat blade screwdriver into the upper tube. The screwdriver will engage the Vari-Adjust plunger at the bottom of the upper tube.
4. From full counterclockwise (80mm travel), 43 turns clockwise are required to achieve 125mm travel. Use the chart below as a guide when adjusting travel.

<b>Fork Travel</b>	<b>Turns from 80mm Travel</b>
90 mm	10 Turns
100 mm	20 Turns
110 mm	30 Turns
125 mm	43 Turns

5. Re-install spring and top cap. Torque top cap to 40 in-lb.
6. To maximize available travel, it may be necessary to change spring rate. Be sure to check your sag following any change in travel.

### External Rebound Adjustment

To change the rebound damping on your Psylo, locate the adjuster knob on the lower right leg. A clockwise adjustment will increase the rebound damping; a counterclockwise adjustment will decrease the rebound damping. Small changes in knob position will make large changes on the trail. Start in the middle, and increase or decrease as necessary.

### Climb-It Control

To change the compression damping adjustment on your Psylo, locate the red adjuster knob on top of the right leg. A clockwise adjustment will increase the compression damping. Turning the adjuster completely clockwise will provide "On-The-Fly Lockout" to minimize movement while sprinting or climbing. Incorporated into the Lockout system is a big hit blow-off feature, allowing for fork movement in the event of an unsuspected change in terrain.

# MAINTENANCE

To maintain the high performance, safety, and long life of your fork, periodic maintenance is required. If you ride in extreme conditions, maintenance should be performed more frequently.

## Before Every Ride

Check the other components on your bicycle in accordance with the manuals supplied by the manufacturer to make sure they are in working order.

## After Every Ride

Clean and dry the exterior of your fork. Avoid directing water pressure at the upper tube/XXX seal junction.

## Every 25 hours of Riding (Fig. 4)

- Using a small blade screwdriver, carefully push the XXX seal up from the lower tubes. Saturate the foam wiper with RockShox RedRum\*. Refit wiper in lower tube.  
NOTE: TO PREVENT SCRATCHING THE UPPER TUBES, COVER THE SCREWDRIVER TIP WITH A SOFT CLOTH. CAREFULLY LIFT THE FOAM LUBRICATION RING. ENSURE THAT THE FOAM RING IS CLEAN AND FREE OF DEBRIS.
- Check top cap assemblies, brake post bolts, and shaft bolts for proper torque.

### Torque Tightening Values

Top Caps	40 in-lb
Brake Posts	80 in-lb
Shaft Bolts	50 in-lb

## Every 50 Hours of Riding

NOTE: SERVICE ON YOUR PSYLO CAN BE PERFORMED WITH IT STILL INSTALLED ON YOUR BICYCLE. YOU WILL NEED TO DISCONNECT THE FRONT BRAKE CABLE AND REMOVE THE WHEEL.

### Tools required

- 5mm Hex Wrench
- Plastic Face Mallet
- Safety Glasses
- Internal Snap Ring Pliers
- Small Flat Blade Screwdriver
- Torque Wrench
- 24mm 6-point Socket
- RockShox 5 wt. Oil
- RockShox Judy Butter
- RockShox RedRum

### REMOVE SPRING STACK (FIGS. 1-2,4)

- Using a 24mm socket remove the top cap from the left leg.
- Remove the coil spring from the left leg.
- Using a small blade screwdriver, carefully push the XXX seal (gray) up from the lower tubes.

NOTE: TO PREVENT SCRATCHING THE UPPER TUBES, COVER THE SCREWDRIVER TIP WITH A SOFT CLOTH. CAREFULLY LIFT THE FOAM LUBRICATION RING. ENSURE THAT THE FOAM RING IS CLEAN AND FREE OF DEBRIS. LEAVE EACH ON UPPER TUBE.

### REMOVE LOWER TUBE ASSEMBLY (FIG. 5)

- Gently pull downward to remove rebound adjuster knob.
- Loosen shaft bolts 5 turns and tap firmly with a plastic faced mallet to separate the shafts from the lower tubes.
- Keep a bucket nearby to catch oil. Inspect the condition of removed oil. If the oil is opaque and/or milky (water contamination), the lower tube assembly should be cleaned.
- Remove shaft bolts.
- Carefully slide lower tube assembly off of upper tubes.



Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5

### CLEAN LOWER TUBE ASSEMBLY

9. Use a biodegradable solvent (Simple Green, Pedro's, or equivalent) and a 12" long, 1/4" diameter soft bristle bottle brush to clean the lower tube internals. Dry thoroughly.

### REMOVE VARI-ADJUST PLUNGER (FIG. 6)

10. Using internal snap ring pliers, remove the retaining ring from the bottom of the upper tube.
11. Slide the Vari-Adjust plunger assembly (left side, rider's perspective) out of the upper tube.
12. Clean plunger thoroughly.

### INSTALL VARI-ADJUST PLUNGER SHAFT

13. Install plunger shaft assembly (left leg, rider's perspective) through the bottom of the upper tube.
14. Re-install the retaining ring in the upper tube.
15. Grease the entire outside diameter of the coil spring with a thin coat of Judy butter.
16. Install coil spring and top cap.
17. Torque top cap to 40 in-lbs.

### INSTALL LOWER TUBE ASSEMBLY

18. Slide cleaned XXX seal and foam filter onto upper tubes.
19. Carefully slide the lower tube assembly onto the upper tubes until just before the lower bushing engages with the upper tube.

### REFILL FLUIDS (FIGS. 7-9)

20. With the fork inverted, pour 10 cc 5 wt. oil through the right (rider's perspective) lower shaft bolt hole and 20 cc 5 wt. oil through the left lower shaft bolt hole.
21. Slide the lower legs onto the upper tube until they engage with the damper and neutral shafts.
22. Install the shaft bolts (hollow bolt on the right side). Torque to 50 in-lbs.
23. Install damper adjuster knob
24. Install foam ring and XXX seal, pressing the XXX seal flush with the lower leg assembly. A small cable tie inserted between the upper tube and the seal will help eliminate air build-up behind the seal on installation. Remove the cable tie following seal installation.
25. Reconnect and adjust front brake cable according to manufacturer's instructions.

## PURE DAMPING SYSTEM

Your fork uses a Pure Damping System. With the red Climb-It control lever turned completely clockwise, only a minimal amount of fork movement should be felt. While standing astride the bicycle, press down on the handlebars quickly. A maximum of 6 mm fork movement should be obtainable. Remember, your fork has a blow-off feature for big hits. Some riders may be able to activate the blow-off and achieve more than 6 mm of travel.

When checking the lockout, light to medium pressure on the handlebars best simulates real world riding conditions.

To maintain Lockout control and damping quality, the Pure Damping system should be rebuilt once a year. Only a qualified bicycle mechanic with proper tools should perform a rebuild of the Pure Damping System.

For more detailed service information, contact your local RockShox dealer or visit [www.rockshox.com](http://www.rockshox.com).



Fig. 6



Fig. 7



Fig. 8



Fig. 9

## WARRANTY

RockShox, Inc. warrants its products for a period of one year from original date of purchase to be free from defects in materials or workmanship. Any RockShox product that is returned to the factory and is found by RockShox to be defective in materials or workmanship will be repaired or replaced at the option of RockShox, Inc. This warranty is the sole and exclusive remedy. RockShox shall not be held liable for any indirect, special, or consequential damages.

The warranty does not apply to products which have not been properly installed and adjusted according to RockShox installation instructions. The warranty does not cover any product that has been subject to misuse or whose serial number has been altered, defaced or removed. This warranty does not cover paint damage or modifications to the product. Proof of purchase is required.

### Warranty Repair

If for any reason it should be necessary to have warranty work done, return the product to the place of purchase. In the USA, Dealers should call for a Return Authorization number (RA#) prior to returning product.

Products returned for inspection must be sent freight prepaid and with proof of purchase to:

RockShox, Inc.  
1610 Garden of the Gods  
Colorado Springs, CO 80907

For more technical information, visit our website at [www.rockshox.com](http://www.rockshox.com). For toll-free technical support in the USA, call 1.800.677.7177. Customers in countries other than the USA should contact their local dealer or distributor.

## INTERNATIONAL DISTRIBUTOR LIST

### Argentina

Broni S.A.  
Phone: 54 11 4292 3000  
FAX: 54 11 4292 4453  
J.J. PASO 1260, (1832) LOMAS DE ZAMORA,  
BUENOS AIRES

### Australia

Steve Cramer Products  
Phone: 61 3 9587 1466  
FAX: 61 3 9587 2018  
39 INDUSTRIAL DRIVE BRAESIDE, VICTORIA 3192

### Austria

Barisitz-Austria  
Phone: 43 512 39 22 87  
FAX: 43 512 39 45 19  
BERNHARD-HOEFELSTRASSE 14, A-6020, INNSBRUCK

### Belgium

Vertex Cycle Systems BV  
Phone: 31 23 57 18184  
FAX: 31 23 57 18606  
FLEMINGSTRAAT 100A, 2041 VL ZANDVOORT  
HOLLAND

### Canada

Bell Sports Canada  
Phone: 403 273 1427 (Calgary)  
FAX: 403 248 1221  
BAY 147, 2760 45TH AVE SE  
CALGARY, ALBERTA  
T2B 3M1

### Chile

Bicicletas Belda Limitada  
Phone: 56 32 881799  
FAX: 56 32 978799  
14 NORTE 1001  
VINA DEL MAR

### Colombia

Disandina Ltda.  
Phone: 574-288-8322  
FAX: 574-288-6211  
CIUDADELA INDUSTRIAL, SIERRA MORENA BODEGA  
No. 207, CRA. 43 A No. 61 SIR 152, SABANETA

### Costa Rica

Inversiones Y Sistemas Garvi  
Phone: 506 296 3383  
FAX: 506 289 7013  
P.O. BOX 4805-1000, SAN JOSE

### Czech Republic

Vanek Praha  
Phone: 42 0 312 698 1889  
FAX: 42 0 312 698 025  
CERRENY UJEZD 185, UNHOST, 27351

### Denmark

Duell A/S  
Phone: 45 86 36 7800  
FAX: 45 86 36 7377  
MOLLERUPVEJ 3, TAASTRUP, 8410 RONDE

### Ecuador

Bici Sport  
Phone: 5932 248737  
FAX: 5932 253691  
AV DE DICIEMBRE 6327, ENTRE LOUVRE Y TOMAS DE,  
BERLANGA.LOCAL #3, QUITO

### Estonia

Hawaii Express  
Phone: 372 6 398 508  
FAX: 372 6 398 566  
REGATI 1, 5K-102, TALLINN, 11911, Estonia  
Or  
Estonian Unidream  
Phone: 372 636 7470  
FAX: 372 636 7470  
Paavli 2A, Tallinn  
EE0004, Estonia

### Finland

Mr. Cool OY  
Phone: 358 9 3250817  
FAX: 358 9 3250609  
LINNAVUORENTIE 28, HELSINKI, 00950

### France

Royal Velo France  
Phone: 33 325 433 730  
Fax: 33 325 43 95 95  
4 RUE DES AZALEES, P.A. SUD-CHAMPANGE  
ST THIBAUT, 10800

### Germany

Sport Import GmbH  
Phone: 49 44 05 9280 0  
FAX: 49 44 05 9280 49  
INDUSTRIESTRASSE 41 B, EDEWECHT, 26188

### Greece

Gatsoulis Stefanos Imports  
Phone: 30 12512 779  
FAX: 30 12533 960  
8 THESSALONIKIS STREET, NEW FILADELPHIA,  
ATHENS, T.T. 14342

### Guatemala

BYS Importaciones S.A.  
Phone: 502 366 7709  
FAX: 502 363 3918  
18 CALLE 7-48, ZONA 10, GUATEMALA

### Holland

Vertex Cycle Systems BV  
Phone: 31 23 57 18184  
FAX: 31 23 57 18606  
FLEMINGSTRAAT 100A, 2041 VL ZANDVOORT  
HOLLAND

### Hong Kong

Flying Ball Bicycle Company  
Phone: 852 23813661  
FAX: 852 23974406  
201 TUNG CHOI ST. G/F, MONGKOK KOWLOON

### Hungary

Prokero Ltd Co.  
Phone: 361 331 3184  
FAX: 361 331 3184  
KALMAN IMRE UTCA 23, BUDAPEST, 1054

**Iceland**

Orninn Hjol Ltd  
Phone: 354 588 9892  
FAX: 354 588 9896  
SKEIFAN 11, P.O. BOX 8036, REYKJAVIK

**Ireland**

Madison  
Phone: 44 181 385 3385  
Fax: 44 208 345 3443  
BUCKINGHAME HOUSE EAST, THE BROADWAY  
STANMORE, MIDDLESEX HA7 4EA  
UNITED KINGDOM

**Israel**

S.I. Noam  
Phone: 972 3659 7928  
Fax: 972 3659 7928  
4 HA'ATZMAUT AVE,  
BAT-YAM, ISRAEL  
59441

**Italy**

Motorquality  
Phone: 39 02 24 951 1  
FAX: 39 02 24 951 228  
20099 SESTO S. GIOVANNI, (MI) I VIA VENEZIA,  
(ANG. VIA CARDUCCI), MILANO

**Japan**

Yoshigai Corporation  
Phone: 81 729 88 5461  
FAX: 81 729 88 5463  
5-19, 1-CHOME, SHIMOROKUMANGI-CHO, HIGASHI-  
OSAKA JAPAN 579

**Korea**

KS Sports  
Phone: 822 548 5408  
FAX: 822 512 3230  
SHIN SEUNG BLDG 4TH FLR, 115-4 NONHYUN-DONG,  
KANGNAM-KU, SEOUL

**Latvia**

Veloserviss  
Phone: 371 750 1292  
Fax: 371 750 1298  
1/1 HAPSALAS ST., RIGA, LV-1005

**Luxembourg**

Vertex Cycle Systems BV  
Phone: 31 23 57 18184  
FAX: 31 23 57 18606  
FLEMINGSTRAAT 100A, 2041 VL ZANDVOORT  
HOLLAND

**Mexico**

Tekno Bike  
Phone: 52 8 336 5602  
FAX: 52 8 338 5663  
HUMBERTO LOBO #780, COL. DEL VALLE, GARZA  
GARCIA, MEXICO, CP, 66220, Mexico

**New Zealand**

W.H. Whorrall & Co. Ltd.  
Phone: 64 9 63 6 06 41  
FAX: 64 9 63 6 06 31  
43 FELIX ST  
PENROSE, AUCKLAND  
NEW ZEALAND

**Norway**

Hallman Sports  
Phone: 46 18 56 16 00  
FAX: 46 18 50 03 22  
HALLNASGATAN 8, S-75228 UPPSALA, SWEDEN

**Panama**

Distribuidora Rali S.A.  
Phone: 507 220-3844  
FAX: 507 220-5303  
VIA ESPANS EDIFICA CARCEP, P.O. BOX 87-0852,  
PANAMA 7

**Peru**

Rojo Sports  
Phone: 511 447 0838  
FAX: 511 447 0838  
AV. REPUBLICA DE, PANAMA 6513, LIMA 33

**Poland**

Giant Polska S.P. ZOO  
Phone: 48 22 645 14 34  
FAX: 48 22 645 14 36  
AL NIEPODLEGLOSCI 221-4, 02-087 WARSZAWA

**Portugal**

Bicimax  
Phone: 351 44 553276  
FAX: 351 44 553187  
APARTADO 34, 2431 MARINHA GRANDE

**Russia**

Sportex  
Phone: 7095 288 4524  
FAX: 7095 288 6888  
KUDRINSKAYA PL., 1,, P.O.BOX 33, MOSCOW,  
123242

**St. Maarten**

Tri-Sport International  
Phone: 5995 43462  
FAX: 5995 43928  
8 AIRPORT BOULEVARD, SIMPSON BAY, NAMIBIA

**Singapore**

Treknology Bikes 3  
Phone: 65 466 2673  
FAX: 65 466 7610  
24 HOLLAND GROVE ROAD, SINGAPORE, 1545

**Slovak Republic**

Paul Lange Oslany  
Phone: 42 1 862 5492 344  
FAX: 42 1 862 5492 350  
MIEROVA 854/37 OSLANY, 97247 SLOVAKIA

**Slovenia**

Proloco Trade  
Phone: 386 64 380 200  
FAX: 386 64 380 222  
ENOTA KRANJ, BRITOF 96A, 4000 KRANJ

**South Africa**

Coolheat (SA) (PTY) Ltd.  
Phone: 27 11 807 5282  
FAX: 27 11 807 2998  
3 RUARGH STREET, PARK CENTRAL, P O BOX 740,  
JOHANNESBURG 2001

**Spain**

K. Motor Dealer S.L.  
Phone: 34 9 1 637 70 97  
FAX: 34 9 1 637 72 64  
PARQUE INDUSTRIAL, EUROPOLIS EDIFICO BRUSELA,  
BLOQUE 4, NAVE 1, LAS ROZAS (MADRID), N/A,  
28230

**Sweden**

Hallman Sports  
Phone: 46 18 56 16 00  
FAX: 46 18 50 03 22  
HALLNASGATAN 8, S-75228 UPPSALA

**Switzerland**

Cilo Bike Service SA  
Phone: 41 21 641 63 30  
FAX: 41 21 641 63 82  
CH. DE L'ORIO 30 A, CASE POSTALE 64, CH- 1032  
ROMANEL S. LAUSANNE

**Taiwan**

Biketech Co. Ltd.  
Phone: 886 22 694 5806  
FAX: 886 22 694 6133  
NO. 12 FU TEH ROAD, 266 LANE, 37 ALLEY HSICHIH,  
TAIPEI HSIEN, TAIWAN, R.O.C.

**Thailand**

Probike Co. Ltd.  
Phone: 662 254 1077  
FAX: 662 254 1078  
237/2 SARASIN ROAD, LUMPINNE, PATUMWAN,  
BANGKOK, 10330

**Turkey**

EBSAT  
Phone: 90 212 514 0525  
FAX: 90 212 519 4846  
EBSAT EMEK BISKLET, EBUSUUD CAD NO.67, 34410  
SIRKECI, ISTANBUL, 34410

**United Kingdom**

Madison  
Phone: 44 181 385 3385  
Fax: 44 208 345 3443  
BUCKINGHAME HOUSE EAST, THE BROADWAY  
STANMORE, MIDDLESEX HA7 4EA  
UNITED KINGDOM

**Uruguay**

International Sports  
Phone: 5982 782498  
FAX: 5982 622532  
AVDA. BRASIL 2567, 11800 MONTEVIDEO

**Venezuela**

Bike Sports  
Phone 582 751 9709  
FAX: 582 753 5071  
CENTRO COMERCIAL IBARRA, PLANTA BAJA, LOCAL  
3-A CALLE GARCILAZO, COLINAS DE BELLO, O,  
CARACAS